

KÄRCHER

makes a difference



RUGGED AND POWERFUL CLEANING POWER.

Roll cage, gas/diesel-powered, cold water pressure washers.

HD PB / PEB / D CAGE



Extra rugged and powerful.

Our roll cage models are the most powerful units in our cold water line, with cleaning power of up to 5000 PSI. Protected by either a rugged powder coated roll cage built of 1-1/4" steel or a corrosion-resistant stainless steel cage, these units feature powerful Vanguard, Honda or Kohler engines, tri-plunger oil bath Kärcher pumps, flat-free tires, and an extra rugged belt-drive assembly with notched V belts and cast iron pulleys.



Diesel model HD 3.4/30 D Cage with optional hose reel

1 Powerful and durable

- Safety thermal pump saver valve protects against hot-water damage by venting recirculated water.
- Rugged roll cage and chassis made of 1 1/4-inch steel and powder coated with an epoxy finish for all-weather protection for PB and PEB models.
- Corrosion-resistant stainless steel frame for D cage model only.
- Reliable Honda, Vanguard or new Kohler engine - model HD 3.4/30 D Cage (Shown above)
- Industrial-grade, tri-plunger, oil-bath Kärcher high pressure pump with forged brass head and ceramic pistons; backed by 7-year warranty.
- Notched V-belts and cast-iron pulleys reduce belt slippage and provide longer pump life.
- 50' durable wire-braid hose rated for 4000 or 6000 PSI; with hose guard for burst protection
- Inlet strainer protects pump from debris in the water source.

2 Smart features

- Five conveniently mounted, quick-couple spray nozzles for varying fan spray.
- Totally enclosed, OSHA-compliant, high-impact polyethylene belt guard and easy-to-adjust belt tension device.
- Insulated, high-pressure trigger gun for hours of fatigue-free cleaning.

3 Outstanding mobility

- Heavy-duty lifting beam for ease in loading and transporting.
- 13" tubed pneumatic tires with steel rims, on PB and PEB models, for easy maneuvering on all terrains and to absorb vibration.
- Flat-free tires on D Cage model only.

TECHNICAL DATA AND EQUIPMENT

TECHNICAL DATA

Model	Part No.	GPM	PSI	Drive	CC	Engine	Fuel	Pump	Ship Weight (lbs)	Ship Dimensions (L x W x H) Inches
HD 3.7/35 PB Cage	1.575-205.0	3.7	3500	Belt	389	Honda GX390	Gas	Kärcher KM	350	42 x 26 x 30
HD 4.0/40 PB Cage	1.575-207.0	4.0	4000	Belt	479	Vanguard 16	Gas	Kärcher KT	470	42 x 26 x 30
HD 4.0/50 PeB Cage*	1.575-200.0	4.0	5000	Belt	688	Honda GX630	Gas	Kärcher KX	495	42 x 26 x 30
HD 4.5/50 PeB Cage*	1.575-201.0	4.5	5000	Belt	688	Honda GX690	Gas	Kärcher KX	500	42 x 26 x 30
HD 3.4/30 D Cage	1.107-373.0	3.4	3000	Belt	442	Kohler KD440	Diesel	LM3540R.3	195	50 x 40 x 50

OPTIONS (FIELD INSTALLED)

Order No.	Description
<input type="checkbox"/> 9.801-028.0	100' EZEE Hose Reel kit, single axle (hose not Included)
<input type="checkbox"/> 9.801-029.0	100' Hose Reel kit, 5000 psi, double axle (hose not Included)
<input type="checkbox"/> 8.750-682.0	100' capacity Hose Reel fixed base (for HD 3.4/30 D Cage model only)
<input type="checkbox"/> 8.929-070.0	Skid feet (for HD 3.4/30 D Cage model only)

Please contact us for more information:

North America

4555 Airport Way
Denver, CO 80239
U.S.A.

Phone 888-805-9852
Fax 800-248-8409

www.karcher.com/us

Kärcher Canada

275 Pendant Drive
Mississauga, ON L5T 2W9
Canada

Tel. 905-364-5006
Fax 905-672-3155

www.karcher.ca